

Section A-6									
Dorot Bronze - 45 & 91 Series									
Valve Size		20mm	25mm	40mm	50mm	80mm	40mm	50mm	80mm
Conn Type	Code	BSP	BSP	BSP	BSP	BSP	BSP - A	BSP - A	BSP - A
Model		D45-34	D45-1	D45-15	D45-2	D45-323	D91-15	D91-2	D91-323
	Price								
Basic Valve		180.00	190.00	338.00	420.00	614.00	341.00	412.50	613.46
Manual Control Valve	M	259.00	265.00	406.00	508.00	676.00	429.00	475.00	676.92
Electric Solenoid 3-Way Irrigation	EL3W	341.00	346.50	484.00	547.80	759.00	517.00	492.50	693.00
Electric Solenoid 3-Way Industrial	EL1	385.00	390.50	528.00	587.50	851.00	561.00	640.00	851.44
Press.Red. 3-Way 29-100 Pilot	PR3W	385.00	390.50	528.00	607.00	863.00	561.00	662.00	863.00
Pressure Reducing Electric 3-Way Plastic Pilot	PREL3W	511.50	540.00	671.00	734.80	946.00	687.50	679.50	880.00
Press Reducing 2-Way Watts Plastic Pilot	PR2W	354.20	360.00	468.00	550.00	744.00	484.00	542.50	743.00
Pressure Reducing 2-Way Dorot Brass Pilot	PR2WB	750.00	750.00	925.00	1,007.00	1,201.00	928.00	999.50	1,222.70
Pressure Sustaining 2-Way Dorot Brass Pilot	PS2WB	750.00	750.00	925.00	1,007.00	1,201.00	928.00	999.50	1,222.70
Pressure Sustaining 3-Way Plastic Pilot	PS3W	385.00	390.50	538.00	607.00	863.00	561.00	662.00	863.00
Pressure Reducing & Sustaining 3-Way Plastic Pilots	PRPS3W	594.00	599.50	780.00	794.00	1,050.00	764.50	849.00	987.00
Float Level Control	FL	253.00	258.50	396.00	506.00	693.00	451.00	456.50	772.12
Optional Additions									
Sagiv Manual Override		55.00	55.00	55.00	55.00	55.00	55.00	55.00	55.00
Copper Plumbing		55.00	55.00	55.00	55.00	55.00	55.00	55.00	55.00
Downstream Venting		5.00	5.00	5.00	5.00	10.00	10.00	10.00	10.00
Industrial Solenoid		40.00	40.00	40.00	40.00	40.00	40.00	40.00	40.00
Isolating Ball Valves		28.00	28.00	28.00	28.00	28.00	28.00	28.00	28.00
Pressure Gauge		37.37	37.37	37.37	37.37	37.37	37.37	37.37	37.37
Pressure Gauge Port		5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00
Brass Base D29-110 Pilot		43.00	43.00	43.00	43.00	43.00	43.00	43.00	43.00
Notes									
- Standard plastic plumbed valves are 10 bar pressure rated.									
- Copper plumbed valves with metal pilots are 16 bar pressure rated.									
- All control valves are fitted with self flushing finger filters.									
- Other control options are available. See your Dorot catalogue for details.									
- All solenoid valves have a built in manual override.									
- For electric valves please state voltage when ordering.									

Auckland NZ
 PH: (09) 919 7600
 FAX: (09) 919 7604

Distributed by: **aquaspec**
 www.aquaspec.co.nz 0800 353 966

Christchurch NZ
 PH: (03) 968 3230
 FAX: (03) 968 3231

Section A-7								
Dorot Cast Iron Angle 39, 82 & 84 Series								
Valve Size		40mm	50mm	80mm	80mm	80mm	80mm	100mm
Conn Type	Code	BSP	BSP	BSP	BSP	BSP	FL	FL
Model		D84-15	D84-2	D84-323	D84-3	D39-3	D82-3	D82-4
	Price							
Basic Valve		192.5	198	308	442.6	540	520.71	830.5
Manual Control Valve	M	280.5	300	396	572.78	627	650	970
Electric Solenoid 3-Way Irrigation	EL3W	375	420	520	676.92	715	765	1050
Electric Solenoid 3-Way Industrial	EL1	415	460	560	803	759	805	1,100.00
Pressure Reducing 3-Way D29-100	PR3W	467	467	550	722.5	759	837	1,070.00
Pressure Reducing Electric D29-100 Pilot	PREL3W	562	575	695	866.98	885.5	940.5	1,170.00
Pressure Reducing 2-Way Watts Plastic Pilot	PR2W	346.5	352	462	572	693	650	960
Pressure Reducing 2-Way Brass Pilot	PR2WB	779	785	930	1,039.50	1,028.50	1,237.00	1,557.00
Press Sustaining 2-Way Brass Pilot	PS2WB	779	785	930	1,039.50	1,028.50	1,237.00	1,557.00
Pressure Sustaining 3-Way D29-200	PS3W	562	467	550	742	759	826.63	1,070.00
Press.Reducing & Sustaining 3way Plastic	PRPS3W	654	665	715	937.28	962.5	1024	1,286.15
Float Level Control	FL	335	335	500	715.98	660	846.15	1145
Optional Additions								
Sagiv Manual Override		55	55	55	55	55	55	55
Copper Plumbing		55	55	55	55	55	55	55
Downstream Venting		5	5	10	10	10	10	10
Industrial Solenoid		40	40	40	40	40	40	40
Isolating Ball Valves		28	28	28	28	28	28	28
Pressure Gauge		37.37	37.37	37.37	37.37	37.37	37.37	37.37
Pressure Gauge Port		5	5	5	5	5	5	5
Brass Base D29-110 Pilot		43	43	43	43	43	43	43
Notes								
- Standard plastic plumbed valves are 10 bar pressure rated.								
- All control valves are fitted with self flushing finger filters.								
- Other control options are available. See your Dorot catalogue for details.								
- All solenoid valves have a built in manual override.								
- For electric valves please state voltage when ordering.								

Auckland NZ
 PH: (09) 919 7600
 FAX: (09) 919 7604

Distributed by: **aquaspec**
 www.aquaspec.co.nz 0800 353 966

Christchurch NZ
 PH: (03) 968 3230
 FAX: (03) 968 3231

Section A-8								
Dorot Cast Iron - 44 & 47 Series								
Valve Size		40mm	50mm	80mm	80mm	50mm	80mm	100mm
Conn Type	Code	BSP	BSP	BSP	BSP	FL	FL	FL
Model		D44-15	D44-2	D44-323	D44-3	D47-2	D47-3	D47-4
	Price							
Basic Valve		150	182.25	285	450	225	500	858
Manual Control Valve	M	270	312.43	423.5	572.78	341	650	980
Electric Solenoid 3-Way Irrigation	EL3W	370	416.57	515	677	429	799	1,100.00
Electric Solenoid 3-Way Industrial	EL1	410	456	555	803	473	785	1,140.00
Pressure Reducing 3-Way 29-100	PR3W	416	463	555	720	488	910	1,110.00
Pressure Reducing Electric 3-Way D29-100	PREL3W	540.24	585.8	682	800	610	910	1,204.50
Pressure Reducing 2-Way Watts Plastic Pilot	PR2W	280	340	415	580	355	780	988.00
Pressure Reducing 2-Way Brass Pilots	PR2WB	787	850	935	1,157.00	928	1,237.00	1,567.00
Pressure Sustaining 2-Way Brass Pilots	PS2WB	787	850	935	1,157.00	928	1,237.00	1,567.00
Pressure Sustaining 3 Way D29-200	PS3W	423	463	555	720	488	785	1,110.00
Pressure Reducing & Sustaining 3-Way Plastic	PRPS3W	618.35	665.21	759	937.00	689	985.00	1,295.00
Float Level Control	FL	455.62	520.71	585.8	716	406.15	820	1100
Optional Additions								
Sagiv Manual Override		55	55	55	55	55	55	55
Copper Plumbing		55	55	55	55	55	55	55
Downstream Venting		5	5	10	10	10	10	10
Industrial Solenoid		40	40	40	40	40	40	40
Isolating Ball Valves		28	28	28	28	28	28	28
Pressure Gauge		37.37	37.37	37.37	37.37	37.37	37.37	37.37
Pressure Gauge Port		5	5	5	5	5	5	5
Brass Base D29-110 Pilot		43	43	43	43	43	43	43

Auckland NZ
 PH: (09) 919 7600
 FAX: (09) 919 7604

Distributed by: **aquaspec**
 www.aquaspec.co.nz 0800 353 966

Christchurch NZ
 PH: (03) 968 3230
 FAX: (03) 968 3231

Section A-9									
Dorot Plastic 75, 95 & 96 Series									
Valve Size		20mm	25mm	40mm	50mm	80mm	80mm	80mm	100mm
Conn Type	Code	BSP	BSP	BSP	BSP	BSP	BSP	SLIP	SLIP
Model		D75-34	D75-1	D75-15	D75-2	D75-3	D95-3	D96-3	D96-4
	Price								
Basic Valve		72	72	130	150	360	535	535	700
Electric Solenoid 2-Way	EL	87	87	204.27	253.67	407.25	NA	NA	NA
Electric Solenoid 3-Way Irrigation	EL3W	233	233	290	320	484	760	760	935
Electric Solenoid 3- Way Industrial	EL1	285	285	340	360	540	800	800	979
Pressure Reducing 3-Way	PR3W	275	275	345	416	550	803	803	989
Pressure Reducing Electric 3-Way Dorot Plastic Pilot	PREL3W	420	420	480	520	690	935	935	1,120.00
Pressure Reducing 2-Way Watts Plastic Pilot	PR2W	240	240	312	334	520	765	765	895
Pressure Reducing/Electric 2-Way Watts Plastic Pilot	PREL2W	314	314	386	408	620	845	845	995.00
Pressure Sustaining 3 Way	PS3W	275	275	345	416	550	803	803	989
Pressure Sustaining Electric 3 Way	PSEL3W	420	420	480	520	690	935	935	1,120.00
Pressure Reducing & Sustaining 3-Way	PRPS3W	NA	NA	566.5	620	770	1,006.00	1,006.00	1,155.00
Electric Pressure Reducing & Sustaining 3-Way	PRPSEL3W	NA	NA	690	730	880	1,117.00	1,117.00	1,282.00
Float Level Control	FL	165	165	220	245	462	690	690	890
Optional Additions									
Sagiv Manual Override		55	55	55	55	55	55	55	55
Downstream Venting		5	5	5	5	10	10	10	10
Pressure Gauge		37.37	37.37	37.37	37.37	37.37	37.37	37.37	37.37
Pressure Gauge Port		5	5	5	5	5	5	5	5
Throttling Handle		10	10	10	10	10	10	10	10
Notes									
- D75 series plastic valves are 10 bar pressure rated.									
- D95 & D96 series PVC valves are 8 bar pressure rated.									
- All control valves over 25 mm are fitted with self flushing finger filters									
- Other control options are available. Refer your Dorot catalogue or contact Aquaspec for details.									
- Electric 2 - way solenoid valves 40 - 80 mm are supplied complete with throttling handle.									
- All solenoid valves have a built in manual override.									
- For electric valves please state voltage when ordering.									
- Other control options are available. See your Dorot catalogue for details.									
- Backflushing valves are 10 bar pressure rated.									
- All solenoids have built in manual override and self flushing finger filter.									

Auckland NZ
PH: (09) 919 7600
FAX: (09) 919 7604

Distributed
by: **aquaspec**
www.aquaspec.co.nz 0800 353 966

Christchurch NZ
PH: (03) 968 3230
FAX: (03) 968 3231

Section A-9						
Filter/Backflushing Valves						
Valve Size	40mm	50mm	50x50mm	80x50mm	80x50mm	100x80mm
Conn Type	BSP	BSP	BSP	VICT/THD	FL	FL
Model	ADBH40	ADBH50	D51-2	D58-3	D57-3	D57-4
	Price					
Basic Valve	299	790	647	1020	1020	1800
Electric Solenoid 3-Way	514	1005	840	1235	1,235.00	2015
Optional Additions						
Downstream Venting	5	5	5	11	11	11
Fail Safe Spring	24	24	24	24	24	24
Industrial Solenoid	40	40	40	40	40	40
Notes						
- 300 or 500 Dorot series valves available on request.						

Auckland NZ
 PH: (09) 919 7600
 FAX: (09) 919 7604

Distributed by: **aquaspec**
 www.aquaspec.co.nz 0800 353 966

Christchurch NZ
 PH: (03) 968 3230
 FAX: (03) 968 3231

Auckland NZ
PH: (09) 919 7600
FAX: (09) 919 7604

Distributed
by: **aquaspec**
www.aquaspec.co.nz 0800 353 966

Christchurch NZ
PH: (03) 968 3230
FAX: (03) 968 3231