

*Simple,  
convenient,  
economical...  
the versatile  
controller that  
delivers Hunter  
quality to  
smaller sites*



6-station



9-station

**S**ophisticated technology and built-in convenience isn't limited to just the most expensive products. The SRC Plus controller offers a proven track record of Hunter quality and reliability, as well as some of the features you'd assume might only be available on high-priced units. The SRC Plus offers dial programming and a full three programs, each with four start times,

plus such conveniences as a built-in 365-day calendar and a rain sensor bypass circuit—just the right features for the needs of smaller landscapes. Available in either 6- or 9-station models, the SRC Plus is housed in a rugged cabinet that offers a polished, professional look. For economy, simplicity, and dependability...you won't find a better value.

### Features & Benefits



#### Dial programming

Easy program entry for installers and end-users

#### 3 programs (A, B, and C) with multiple start times

Accommodates repeat watering requirements

#### 365-day calendar

Accommodates odd/even watering restrictions, maximum flexibility

#### Rain sensor bypass

Quick override of rain sensor, no separate switch required

#### Large wiring compartment with handy terminal strip

Fast installation, extra space to work

#### Non-volatile memory

Excellent insurance against unreliable power; retains program data without the need for a battery

#### Remote control ready

Supplied with SmartPort® wiring harness for ICR remote control

## Models

SRC-601i – 6-station, Indoor Model without Plug-in Transformer

SRC-901i – 9-station, Indoor Model without Plug-in Transformer

## Options

- Faceplate label and instructions available in English, Spanish, French, and Italian

## Dimensions

- SRC Plus : 21 cm H x 22 cm W x 6 cm D

## Specifications and Features

- Station run time: 0-99 minutes in 1-minute increments
- Start times: 4 per day, per program, for up to 12 daily starts
- Day schedule: 7-day calendar or true odd-even programming with 365-day calendar clock
- AM/PM or 24 hour clock option
- Start time stacking
- One button manual start and advance
- Transformer input: 230VAC, 50 HZ or 120VAC, 60 Hz (transformer not included with export units)
- Transformer output: 24VAC, 0.75A
- Station output: 24VAC, 0.35A per station
- Maximum total output: 24VAC, 0.7A, includes master valve circuit
- Battery: Not required for program backup. 9 volt alkaline battery may be used to program controller in absence of AC power.
- Non-volatile memory for program data (no battery required to maintain program)
- Master valve output: 24VAC, 0.35A
- Surge protection: primary MOV-type
- Rain sensor override compatible with most major brands
- Test program feature allows for quick system checks
- Preset test cycle on program "C"
- UL listed
- Central control compatible with Hunter IMMS™ system
- Hunter Quick Check™ helps troubleshoot field wiring problems
- Electronic Short Circuit Protection; automatically detects and skips shorted stations, no fuses to replace



Compatible with Hunter rain sensors.

## The SRC Plus: As Easy to Install as it is to Use

The SRC Plus controller is easy to use. Even easier to install, with an exceptionally large wiring compartment and a handy provision for conduit, as well as a wall mounting bracket. There's no measuring, no pilot holes, no special templates necessary. Just position the bracket, install two screws (provided), and hang the controller. Once again, easy does it.



## Make Your Simple and Reliable Controller Even Simpler



Now you can make your user-friendly SRC Plus controller even easier to operate with the optional ICR remote control. Imagine the convenience of being able to manually activate any zone from anywhere in a yard—up to one kilometer from the controller. For more information on this handy option, consult Hunter ICR brochure # INT-483 or visit [www.HunterIndustries.com](http://www.HunterIndustries.com).



The SRC's standard indoor cabinet is good looking and extra sturdy, and can be used with or without the protective door.

## SPECIFICATION GUIDE

EXAMPLE: **SRC - 601i**

MODEL	FEATURES
SRC 600i	6-Station Controller, Indoor Model, 50/60 Hz with 110/120 VAC Plug-in Transformer
SRC 900i	9-Station Controller, Indoor Model, 50/60 Hz with 110/120 VAC Plug-in Transformer
SRC 601i	6-Station Controller, Indoor Model, 50/60 Hz without plug-in Transformer
SRC 901i	9-Station Controller, Indoor Model, 50/60 Hz without plug-in Transformer

Auckland NZ  
PH: (09) 919 7600  
FAX: (09) 919 7604

Distributed by: **aquaspec**  
[www.aquaspec.co.nz](http://www.aquaspec.co.nz) 0800 353 966

Christchurch NZ  
PH: (03) 968 3230  
FAX: (03) 968 3231