

mini-Wob **WOBBLERS®**



mini wobbler®

Outstanding performance **for upright applications**

The Senninger mini-Wobbler® employs the same unique off-center rotary-action as the standard Wobbler®. It provides extremely uniform coverage over a large diameter at low pressures. It is constructed entirely of engineering-grade thermoplastics for excellent corrosion resistance.



The mini-Wobbler can be mounted on the Riser Adapter for installation versatility.

- Low evaporative loss
- Multi-level throw, approximate angle: 10°
- Color-coded nozzles for easy size identification
- Flow rates: 0.42 to 2.61 gpm (97.2 to 576.0 L/hr)
- Operating pressures: 15 to 35 psi (1.0 to 2.5 bar)
- Standard inlet: 1/2" NPT male
- Two-year warranty on materials, workmanship AND performance

SPRINKLER BASE PRESSURE	U.S. - Diameter (feet)					METRIC - Diameter (meters)				
	(psi) 15	20	25	30	35	(bar) (psi)	1.0	1.5	2.0	2.5
#4 Nozzle - Light Blue (1/16")						#4 Nozzle - Light Blue (1.59 mm)				
Flow (gpm)	0.42	0.50	0.56	0.62	0.68	(L/hr)	97.2	118.8	136.8	151.2
Diam. at 1.5' height (feet)	26.4	28.0	29.2	30.0	30.4	0.5 m (m)	8.0	8.7	9.1	9.3
Diam. at 3.0' height (feet)	30.8	32.0	32.8	33.6	34.0	1.0 m (m)	9.3	9.8	10.2	10.4
#5 Nozzle - Beige (5/64")						#5 Nozzle - Beige (1.98 mm)				
Flow (gpm)	0.64	0.75	0.84	0.91	0.99	(L/hr)	144.0	176.4	205.2	230.4
Diam. at 1.5' height (feet)	30.8	33.6	34.8	35.6	36.0	0.5 m (m)	9.3	10.4	10.8	11.0
Diam. at 3.0' height (feet)	36.4	39.2	39.4	39.6	39.6	1.0 m (m)	11.0	12.0	12.1	12.1
#6 Nozzle - Gold (3/32")						#6 Nozzle - Gold (2.38 mm)				
Flow (gpm)	0.95	1.10	1.25	1.36	1.47	(L/hr)	216.0	252.0	288.0	324.0
Diam. at 1.5' height (feet)	33.2	36.0	36.8	37.2	37.6	0.5 m (m)	10.0	11.1	11.3	11.5
Diam. at 3.0' height (feet)	39.4	41.8	42.0	42.2	42.2	1.0 m (m)	11.9	12.8	12.8	12.9
#7 Nozzle - Lime (7/64")						#7 Nozzle - Lime (2.78 mm)				
Flow (gpm)	1.30	1.51	1.69	1.86	2.01	(L/hr)	288.0	360.0	396.0	468.0
Diam. at 1.5' height (feet)	34.8	37.6	38.4	38.8	39.2	0.5 m (m)	10.5	11.5	11.8	12.0
Diam. at 3.0' height (feet)	41.0	42.8	43.0	43.0	43.0	1.0 m (m)	12.3	13.1	13.1	13.1
#8 Nozzle - Lavender (1/8")						#8 Nozzle - Lavender (3.18 mm)				
Flow (gpm)	1.67	1.95	2.18	2.39	2.61	(L/hr)	360.0	468.0	540.0	576.0
Diam. at 1.5' height (feet)	35.6	38.4	39.2	39.6	40.0	0.5 m (m)	10.8	11.8	12.0	12.2
Diam. at 3.0' height (feet)	41.4	43.2	43.4	43.4	43.4	1.0 m (m)	12.5	13.2	13.2	13.2

Larger (9/64" and 10/64") diameter nozzles also available. Consult factory.
 Figures reflect data from tests performed in accordance with the American Society of Agricultural Engineers standard S398.1 and are representative of production at the time of publication. Sprinkler performance may vary with actual field conditions. Stream heights range from 1.5 - 3.0 ft (0.5 - 0.9 m) above nozzle based on pressure and nozzle size.
Minimum recommended riser height is 1.5' (0.5 m).



Senninger® Telephone: 407-877-5655 • Fax: 407-905-8249 • Int'l Fax: 407-905-8239
 Web: www.senninger.com • E-Mail: info@senninger.com

Auckland NZ
 PH: (09) 919 7600
 FAX: (09) 919 7604

Distributed by: **aquaspec**
 www.aquaspec.co.nz 0800 353 966

Christchurch NZ
 PH: (03) 968 3230
 FAX: (03) 968 3231

i-mini wobbler®

Outstanding performance **for overhead applications**

The Senninger i-mini-Wobbler® employs the same unique off-center rotary-action as the standard Wobbler®. It provides extremely uniform coverage over a large diameter at low pressures. It is constructed entirely of engineering-grade thermoplastics for excellent corrosion resistance.



The Inverted mini-Wobbler produces a broad, rain-like application.

- Low evaporative loss
- Multi-level throw, approximate angle: 0°
- Color-coded nozzles for easy size identification
- Flow rates: 0.75 to 2.61 gpm (176.4 to 576.0 L/hr)
- Operating pressures: 20 to 35 psi (1.5 to 2.5 bar)
- Standard inlet: 1/2" NPT male
- Two-year warranty on materials, workmanship AND performance

SPRINKLER BASE PRESSURE	(psi)	U.S. - Diameter (feet)				METRIC - Diameter (meters)			
		20	25	30	35	(bar) (psi)	1.5	2.0	2.5
#5 Nozzle - Dark Beige (5/64")									
Flow (gpm)		0.75	0.84	0.91	0.99	(L/hr)	176.4	205.2	230.4
Diam. at 3.0' height (feet)		30.2	30.8	31.2	31.4	1.0 m (m)	9.27	9.48	9.59
Diam. at 6.0' height (feet)		31.8	32.4	32.8	33.2	2.0 m (m)	9.76	9.97	10.2
#6 Nozzle - Dark Gold (3/32")									
Flow (gpm)		1.10	1.25	1.36	1.47	(L/hr)	252.0	288.0	324.0
Diam. at 3.0' height (feet)		30.8	31.4	31.8	32.0	1.0 m (m)	9.45	9.67	9.77
Diam. at 6.0' height (feet)		33.8	34.4	34.8	35.2	2.0 m (m)	10.4	10.6	10.8
#7 Nozzle - Dark Lime (7/64")									
Flow (gpm)		1.51	1.69	1.86	2.01	(L/hr)	360.0	396.0	468.0
Diam. at 3.0' height (feet)		31.2	31.8	32.2	32.4	1.0 m (m)	9.57	9.79	9.89
Diam. at 6.0' height (feet)		35.0	35.6	36.0	36.4	2.0 m (m)	10.7	11.0	11.1
#8 Nozzle - Dark Lavender (1/8")									
Flow (gpm)		1.95	2.18	2.39	2.61	(L/hr)	468.0	540.0	576.0
Diam. at 3.0' height (feet)		31.6	32.2	32.6	32.8	1.0 m (m)	9.70	9.91	10.0
Diam. at 6.0' height (feet)		35.6	36.2	36.6	37.0	2.0 m (m)	10.9	11.1	11.3

Figures reflect data from tests performed in accordance with the American Society of Agricultural Engineers standard S398.1 and are representative of production at the time of publication. Sprinkler performance may vary with actual field conditions. Stream heights range from 0.5 - 1.5 ft (0.2 - 0.5 m) above nozzle based on pressure and nozzle size.



Senninger®

Telephone: 407-877-5655 • Fax: 407-905-8249 • Int'l Fax: 407-905-8239
Web: www.senninger.com • E-Mail: info@senninger.com

Auckland NZ
PH: (09) 919 7600
FAX: (09) 919 7604

Distributed by: **aquaspec**
www.aquaspec.co.nz 0800 353 966

Christchurch NZ
PH: (03) 968 3230
FAX: (03) 968 3231