

SENNINGER WASTEWATER PRODUCTS

- For over 40 years, Senninger has been dedicated to the innovative design and manufacture of quality sprinklers, spray nozzles and pressure regulators.
- Senninger products are depended upon worldwide for wastewater, solid-set, undertree, nursery and center-pivot systems.
- These products are backed by a two-year warranty on materials, workmanship and performance. Nozzle orifices are backed by a five-year warranty.



- Flow range from less than 2 to over 100 gpm.
- Non-brass components eliminate electrolysis.
- Engineering-grade thermoplastics resist chemical degradation, scale buildup and are UV resistant.
- All springs are stainless steel and enclosed to resist contamination.
- Lavender caps designate non-potable water.



**SPECIFY
THE BEST**

*Ask for high quality,
dependable Senninger products.
Consult your local authorized dealer
or contact us at:*

Senninger Irrigation Inc.

Auckland NZ
PH: (09) 919 7600
FAX: (09) 919 7604

Distributed
by: **aquaspec**
www.aquaspec.co.nz 0800 353 966

Christchurch NZ
PH: (03) 968 3230
FAX: (03) 968 3231

Technical Information

FULL CIRCLE IMPACT SPRINKLERS*

30, 40, 50 SERIES

pipe thread: 3/4" NPT male or female
trajectory: 6, 12, 14 or 23 degrees
nozzle sizes: #7 to #18 (7/64" to 18/64")
flow range: 1.68 to 25.6 gpm
base press.: 25 to 65 psi

70 SERIES

(range-drive and spreader-drive models available)

pipe thread: 1" NPT male or female
trajectory: 25 degrees
nozzle sizes: #14 to #24 (7/32" to 3/8")
flow range: 8.11 to 39.1 gpm
base press.: 35 to 70 psi

80 HEAVY-DUTY SERIES

(range-drive and spreader-drive models available)

pipe thread: 1 1/4" NPT male or female
trajectory: 25 degrees
nozzle sizes: #24 to #40 (3/8" to 5/8")
flow range: 23.6 to 106.8 gpm
base press.: 35 to 75 psi

* Most models available in a single or double nozzle configuration



SPRAY NOZZLES

SUPER-SPRAY®

pipe thread: 3/4" NPT male
trajectory: concave, flat & convex pads available
nozzle sizes: #4 to #26 (4/64" to 26/64")
flow range: 0.27 to 24 gpm
base press.: 10 to 40 psi

WOBLER®

pipe thread: 1/2" or 3/4" NPT male
trajectory: standard or low-angle models available
nozzle sizes: #6 to #18 (3/32" to 9/32")
flow range: 0.78 to 13.5 gpm
base press.: 10 to 35 psi

XCEL WOBLER®

pipe thread: 1/2" or 3/4" NPT male
trajectory: high or mid-angle models available
nozzle sizes: #6 to #14 (3/32" to 7/32")
flow range: 0.78 to 7.64 gpm
base press.: 10 to 30 psi

PRESSURE REGULATORS

PMR-LF (Low Flow)

pipe thread: 3/4" NPT female x 3/4" NPT female
preset outlet psi: 1/2 - 5 gpm models available in 6 & 10 psi
1/10 - 8 gpm models available in 12, 15, 20, 25, 30, 35 & 40 psi

PMR-MF (Medium Flow)

pipe thread: 3/4" NPT female x 3/4" NPT female
preset outlet psi: 4 - 16 gpm available in 6 & 10 psi
2 - 20 gpm available in 15, 20, 25, 30, 35, 40, 50 & 60 psi

PR-HF (High Flow)

pipe thread: 1 1/4" NPT female inlet x 1" NPT female outlet
preset outlet psi: 10 - 32 gpm available in 10, 15, 20, 25, 30, 40 & 50 psi

Consult our catalog for more specific performance data on all of the above products.

Auckland NZ
PH: (09) 919 7600
FAX: (09) 919 7604

Distributed by: **aquaspec**
www.aquaspec.co.nz 0800 353 966

Christchurch NZ
PH: (03) 968 3230
FAX: (03) 968 3231